

Common Action's URL parameters

The common format of an action URL is the following:

- `{outputFormat}/{communityUcid}/action/{actionName}/{elementId}/?return-path={returnPath}[&specificParameters]`
- `{outputFormat}` can take the following values:
 - `json` – the result of an action will be formatted into JSON format and wrote into the response
 - `redirect` – after executing an action redirect to the certain page will be performed
- `{actionName}` specifies the action to be executed, required
- `{elementId}` an ucid following the `0` character, can be required or not, depending on type of an action
- `{returnPath}` in case of `redirect` output format defines the redirect URL. If this parameter was not specified, the redirect will be performed to the `UrlReferrer` URL or to the community landing page (if `UrlReferrer` is undefined)

BecomeFriend Action

This action is designed for requesting friendship by logged user to another user.

Access string

- `/action/becomeFriend/?return-path={returnPath}&user={userUcid}&username={userName}&message={message}`
 - `{userUcid}` – ucid of the recipient of the request, optional
 - `{userName}` – loginName of the recipient of the request, required if `{userUcid}` is not specified
 - `{message}` – message of the request

JoinGroup Action

This action allows logged user to become a member of a group.

Access string

- `/action/joinGroup/0{groupUcid}/?return-path={returnPath}`
 - `{groupUcid}` – ucid of the group, required

LeaveGroup Action

This action allows logged user to break his membership in a group.

Access string

- `/action/leaveGroup/0{groupUcid}/?return-path={returnPath}`
 - `{groupUcid}` – ucid of the group, required